

## Everlast 1 Multi-Purpose Lubricant

### **Description**

Everlast 1 is a biodegradable synthetic lubricant for use in valves carrying aliphatic hydrocarbon liquids and gasses, including kerosene, fuel oils, crude distillates (sweet or sour), water, condensate, dilute acids and caustics. It is waterproof and has excellent resistance to oxidation and high metal adhesion. Everlast 1 should be used as a hydrocarbon resistant ball and gate valve lubricant. Everlast 1 is approved by most major valve manufacturers.

### **Applications**

For use in plug, gate and ball valves. Suitable for use in hydrocarbon gasses.

DO NOT use in oxygen service.

### **Features**

- Water resistant
- Fully additive treated
- 100% synthetic
- High metal adhesion
- Inhibited for H<sub>2</sub>S

### **Physical Properties**

- Consistency, Cone Penetration (D-217) 220-300
- Dropping Point, °F (D-566) none
- Oil Separation, % wt. loss (D-1742) 5 max
- Oxidation Stability (D-942) 10 max
- Rust Preventive Test (D-1743) pass
- Temperature range: 40° to 400°F, -40° to 204°C
- Color - brown
- Type Oil - synthetic
- Corrosive Inhibitor - Imidazoline Derivative
- EP Additive - Diester Type

### **Product Code - EV1**