

Everlast 146 Hydrocarbon Resistant

Description

Everlast 146 is a synthetic lubricant formulated for high chemical and mechanical stability to general hydrocarbon service. The synthetic polymer oils used in Everlast 146 make this an excellent all purpose gate valve lubricant and sealant for the oilfield. Everlast 146 is a blend of synthetic oils for use in valves carrying LPG, LNG, aliphatic hydrocarbon liquids and gasses ,including kerosene, fuel oils, crude distillates (sweet or sour), water, condensate, dilute acids and caustics. It is waterproof and has excellent resistance to oxidation and high metal adhesion.

Applications

For use in gate valves. Suitable for use in hydrocarbon liquids and gasses.

DO NOT use in oxygen service.

Features

- Fully additive treated
- 100% synthetic
- Water resistant
- High metal adhesion
- Inhibited for H₂S

Physical Properties

- Consistency, Cone Penetration (D-217) 220 to 300
- Dropping Point, °F (D-566) none
- Oil Separation, % wt. Loss (D-1742) 5 max
- Oxidation Stability (D-942) 10 max
- Rust Preventive Test (D-1743) pass
- Temperature range: -40 to 500°F
- Color - brown
- Type Oil - synthetic
- Corrosive Inhibitor - Imidazoline Derivative
- EP Additive - Diester Type

Product Code - 146